



ProPipe FLEXIBLE DRAINAGE PIPE

DESCRIPTION

ProPipe is a sub surface corrugated drainage pipe manufactured to Australian Standard AS 2439 – 2007 Part 1.

ProPipe is utilised for sub surface drainage of domestic to agricultural projects as well as construction and road projects. The light weight corrugated pipe has regularly punched slotted openings along its entire length to allow efficient drainage. ProPipe is durable and easy to use.

ProPipe installation is dependent on the size and type of project but generally includes the following steps:-

1. Prepare a trench 200mm wider than the ProPipe diameter to be installed.
2. Line the trench with a suitable geotextile filter such as ProFab AS140 grade.
3. Select a suitable clean drainage aggregate to act as a filter and bedding and place into the base of the trench approximately 50mm deep.
4. Place the ProPipe in the trench and backfill with the selected drainage aggregate.
5. Wrap the geotextile filter over the drainage aggregate and backfill to the surface with a light soil cover to a recommended 150mm minimum coverage.
6. If the drainage aggregate or backfill material contains very fine particles, a filtersock can also be included around the ProPipe to further ensure fine material does not enter the pipe. ProPipe is available with RTA grade filtersock for critical road projects and a standard grade filtersock for general applications.

APPLICATIONS

- Road edge drainage
- Retaining wall or collector pipe drainage
- Underground soak well distribution
- Sports field and recreational park drainage
- Residential yard drainage

TYPICAL PROPERTIES

DIAMETER	CLASS	MATERIAL	FLOW & VELOCITY @ GRADIENT		COIL LENGTHS
			i = 0.01	i = 0.001	
65mm	400	HDPE	3.3m ³ /hr @ 0.4m/s	& 1.0m ³ /hr @ 0.1m/s	20m, 200m
100mm	400	HDPE	11.1m ³ /hr @ 0.5m/s	& 3.4m ³ /hr @ 0.2m/s	20m, 100m
100mm	1000	PVC	11.1m ³ /hr @ 0.5m/s	& 3.4m ³ /hr @ 0.2m/s	20m, 100m
160mm	200/400	HDPE/PVC	40.5m ³ /hr @ 0.8m/s	& 12.5m ³ /hr @ 0.2m/s	20m, 60m

All available with standard sock, RTA sock or unsocked configuration and are always slotted unless requested unsocked/unslotted. Other pipe diameters, coil lengths and strength class are available upon request.

DISCLAIMER : All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd have a policy of continuous development so information and product specifications may change without notice. SEP.10

APRIL.16

DISTRIBUTORS OF :

Geotextiles

Geogrids

Dewatering Tubes

Subsoil Drainage

Wick Drains

Erosion Control

Gabions & Rock Mattresses

Industrial Fabrics

Lining Systems



Global Synthetics
Australian Company – Global Expertise

SYDNEY

P: (02) 9725 4321

F: (02) 9725 4304

E: info@globalsynthetics.com.au

BRISBANE

P: (07) 3865 7000

F: (07) 3865 4444

PERTH

P: (08) 9459 4300

F: (08) 9459 4311

MELBOURNE

P: (03) 9791 1772

F: (03) 9791 1776

ADELAIDE

P: (08) 8384 8894

F: (08) 8384 3886

www.globalsynthetics.com.au