



## ProFab® PP WOVEN GEOTEXTILE PP30 & PP80

### DESCRIPTION

ProFab woven geotextiles are manufactured from the extrusion of polypropylene into either a flat tape or bundled tape fabric. These geotextiles have a defined strength in both the roll and cross roll direction. These geotextiles develop strength at relatively low strains.

### APPLICATION

ProFab woven geotextiles are ideally suited for applications of separation of dissimilar materials with a secondary benefit of reinforcement. ProFab woven geotextiles are ideally suitable for the construction of paved and unpaved roads.

### TYPICAL PROPERTIES

MECHANICAL PROPERTIES	TEST METHOD	UNIT	PP30	PP80
Wide Width Tensile Strength XD	ISO 10319	kN/m	30	80
Wide Width Tensile Strength MD	ISO 10319	kN/m	30	80
Strain XD	ISO 10319	%	15	14
Strain MD	ISO 10319	%	20	19
CBR Burst Strength	ISO 12236	kN	3.5	10
HYDRAULIC PROPERTIES				
Pore Size	ISO 12956	mm	0.3	0.3
Nominal Flow Rate	ISO 11058	litres/m <sup>2</sup> /s	23	20
PHYSICAL PROPERTIES				
Mass		g/m <sup>2</sup>	150	360
Roll Size		m	5.85x160	5.85 x 100
Nominal Roll Mass		kg	170	235

DISTRIBUTORS OF :

- Geotextiles**
- Geogrids**
- Dewatering Tubes**
- Subsoil Drainage**
- Wick Drains**
- Erosion Control**
- Gabions & Rock Mattresses**
- Industrial Fabrics**
- Lining Systems**

ProFab is a registered trademark of Global Synthetics Pty Ltd.

Polypropylene is one of the most highly durable polymers known to man. It is resistant to all natural occurring soil acids and alkalis. Polypropylene geotextiles are unaffected by bacteria and fungi. Properties of ProFab geotextiles are typical values and correspond to average values derived from in house and independent laboratory testing.

DISCLAIMER : All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd have a policy of continuous development so information and product specifications may change without notice.

APRIL.16



Global Synthetics

#### SYDNEY

P: (02) 9725 4321

F: (02) 9725 4304

E: [info@globalsynthetics.com.au](mailto:info@globalsynthetics.com.au)

#### BRISBANE

P: (07) 3865 7000

F: (07) 3865 4444

#### PERTH

P: (08) 9459 4300

F: (08) 9459 4311

#### MELBOURNE

P: (03) 9791 1772

F: (03) 9791 1776

#### ADELAIDE

P: (08) 8384 8894

F: (08) 8384 3886

[www.globalsynthetics.com.au](http://www.globalsynthetics.com.au)